



**MATERIAL SAFETY DATA SHEET**  
**T43 NUTLOCK**

Revised Date: January 2009

Page 1 of 4

Infosafe No: 5HO02

Issue Date: June 2005

MODIFIED by HOLDTITE AUSTRALIA

**SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

**Product Name:** HOLDTITE AUSTRALIA T43 NUTLOCK

**Other Names:** T43

**Use:** Anaerobic Sealant

**Part Number:** T4310 (10mls), T4350(50mls), T43250(250mls)

**Supplier:** Holdtite Australia Pty Ltd  
**Address:** 21 Heath Street  
Lonsdale, South Australia, 5160

**Emergency Tel:** +61 1300 552 680  
**Telephone:** +61 8 8186 0844  
**Fax:** +61 8 8186 0252

**Emergency Contact**  
**Name:** Harald Schaaf  
**Emergency Contact**  
**Address:** See Above Address

**Other Information:** The information below is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This Company shall not be held liable for any damage resulting from handling or from contact with the above product.

**SECTION 2. HAZARDOUS IDENTIFICATION**

Classified as hazardous according to criteria of NOHSC.

**Hazard Category:** Irritant

**Risk Phrases:** R36/38 Irritating to eyes, respiratory system and skin.  
R43 May cause sensitization by skin contact

**Safety Phrases:** S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice  
S27 Take off immediately all contaminated clothing.  
S28 After contact with skin, wash immediately with plenty of water  
S3/14 keep in a cool place.  
S3/9/14 Keep in a cool, well ventilated place away from direct sunlight  
S37 Wear suitable gloves  
S37/39 Wear suitable gloves and eye/face protection  
S39 Wear eye/face protection  
S7 Keep container tightly closed  
S9 Keep container in a well ventilated place



# MATERIAL SAFETY DATA SHEET T43 NUTLOCK

Revised Date: January 2009

Page 2 of 4

Infosafe No: 5HO02

Issue Date: June 2005

MODIFIED by HOLDTITE AUSTRALIA

## SECTION 3. COMPOSITION/INFORMATION OF INGREDIENTS

<b>Ingredients</b>	<b>Name</b>	<b>CAS</b>	<b>Proportion</b>	<b>Hazard Symbol</b>	<b>Risk Phrase</b>
	Aromatic Dimethacrylate Ester	24448-20-2	30-60%	Xi	R43
	Dibutyl pthallate	84-74-2	0-35%		
	HYDROXYETHYL METHACRYLATE	868-77-9	1-10%	Xi	R36/38, R43
	Cumene hydroperoxide	80-15-9	0-2%	C+, F	R11, R35

## SECTION 4. FIRST AID MEASURES

<b>Ingestion:</b>	Rinse mouth thoroughly with water immediately. Seek medical advice.
<b>Eye contact:</b>	Immediately irrigate with copious quantity of water for at least 15 minutes. Eyelids to be held open. In all case of eye contamination it is a sensible precaution to seek medical advice.
<b>Skin contact:</b>	Remove contaminated clothing and wash before re-use. Rinse and wash skin with water and soap.
<b>Advice to Doctor:</b>	Treat symptomatically

## SECTION 5. FIRE FIGHTING MEASURES

<b>Extinguishing Media:</b>	Use suitable extinguishing media for the surrounding environment.
<b>Fire/Exposure Hazards:</b>	Fire fighters to wear self-contained breathing apparatus if risk of exposure to vapour or products of combustion.
<b>Hazchem Code:</b>	None allocated

## SECTION 6. ACCIDENTIAL RELEASE MEASURES

Safety boots, gloves and chemical goggles are to be worn if a spill occurs and clean up is needed. For small spills, use a cloth to wipe up residue. For large spills, collect and contain spillage with inert absorbent materials (e.g. sand, earth). Transfer spilled materials to containers that are suitable for storing the spilled material. The areas that the spillage occurred should be adequately flushed with warm soapy water to render the area safe for human contact.



## MATERIAL SAFETY DATA SHEET T43 NUTLOCK

Revised Date: January 2009

Page 3 of 4

Infosafe No: 5HO02

Issue Date: June 2005

MODIFIED by HOLDTITE AUSTRALIA

### SECTION 7. HANDLING AND STORAGE

**Handling:** Use in well ventilated area. Avoid breathing vapour. Observe recommendations in SECTION 8.

**Storage:** Holdtite T43 should be stored in a dry cool area, out of direct sunlight. Optimal Storage temperature: 8°C to 21°C. Stored correctly, this product has a 12 month shelf life from manufacture.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Exposure Limits:** TWA 5mg/m<sup>3</sup> Dibutyl phthalate

**Personal Protection:** Avoid contact with eyes and skin. Wear PVC or rubber gloves and safety glasses. Use with adequate ventilation.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** Blue Liquid

**Flash Point:** 85 Deg C

**Solubility in Water** Slightly soluble

**Density** 1.06

**Odour** Perceptible Odour

### SECTION 10. STABILITY AND REACTIVITY

**Chemical Stability:** Stable under normal conditions of temperature and pressure

**Conditions to Avoid:** Open flames, sparks and strong heat.

**Incompatible Materials:** Keep away from strong oxidising agents, acids and alkalies. Strong reducing agents destabilize this product.

**Hazardous Decomposition Products:** Combustible liquid. Releases noxious fumes, oxides of nitrogen and oxides of carbon in a fire.

**Hazardous Reactions:** Hazardous polymerization will not occur



**MATERIAL SAFETY DATA SHEET**  
**T43 NUTLOCK**

*Revised Date: January 2009*

Page 4 of 4

Infosafe No: 5HO02      Issue Date: June 2005      MODIFIED by HOLDTITE AUSTRALIA

**SECTION 11. TOXICOLOGY INFORMATION**

**HEALTH EFFECTS**

**Acute - Swallowed:**      May cause irritation to mouth, throat and stomach.

**Acute – Eye**              May be an eye irritant. May cause watering of eyes.

**Acute – Skin**             Contact with skin may result in irritation.

**Acute – Inhaled**        may cause irritation to the nose and throat

**SECTION 12. ECOLOGICAL INFORMATION**

This product can be harmful to aquatic organisms. Do not allow to contaminate waterways or soil.

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal**                 Follow state or local authority regulations and guidelines for disposal of the waste. Clean area with detergent and water. Do not allow product to enter drains, sewers or water courses – inform the local authorities if this occurs.

**Container Disposal**    Dispose of as normal industrial waste

**SECTION 14. TRANSPORT INFORMATION**

Not classified as Dangerous Goods according to the ADG Code.

**SECTION 15. REGULATORY INFORMATION**

None Allocated.

**SECTION 16. OTHER INFORMATION**

**Abbreviations/Acronyms**

ADG Code – Australian Code for the Transport of Dangerous Goods by Road and Rail

NOHSC – National Occupational Health and Safety

TWA – Time-Weight Average

**CONTACT POINT**

Technical Contact

Numbers:                 Head Office Tel: 1300 552 680

Technical Contact      Harald Schaaf

\*\*End of MSDS\*\*