

**HOLDIT[®]****MATERIAL SAFETY DATA SHEET
HOLDIT S72**

Revised Date: March 2011

Page 1 of 4

Infosafe No: 5HO0W Issue Date: June 2005

MODIFIED by HOLDTITE AUSTRALIA

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER**Product Name:** HOLDTITE AUSTRALIA S72 PIPESEAL WITH TEFLON**Other Names:** S72**Use:** Slow Cure Pipe Seal**Part Number:** S7250 (50mls), S72250 (250mls)**Supplier:** Holdtite Australia Pty Ltd
Address: 21 Heath Street
Lonsdale, South Australia, 5160**Emergency Tel:** +61 1300 552 680
Telephone: +61 8 8186 0844
Fax: +61 8 8186 0252**Emergency Contact
Address:** See Above Address**Other Information:** The information below is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This Company shall not be held liable for any damage resulting from handling or from contact with the above product.**SECTION 2. HAZARDOUS IDENTIFICATION****2.1 Classification of the substance or mixture****2.1.1 Classification –** Xi; R36/37/38-43
1999/45/EC**Main Hazards** Irritating to eyes, respiratory system and skin. May cause sensitization by skin contact.**SECTION 3. COMPOSITION/INFORMATION OF INGREDIENTS****3.2 Mixtures****67/548/EEC/1999/45/EC**

Chemical name	Index No.	CAS No.	EINECS No.	REACH Reg. No.	Conc. (% w/w)	Classification
2-Hydroxyethyl methacrylate	607-124-00-X	868-77-9	212-782-2		10-20%	Xi; R36/38 R43
Cumene Hydroperoxide	617-002-00-8	80-15-9	201-254-7		0.1-1%	O; R7 T; R23 Xn; R21/22-48/20/22 C; R34 N; R51/53

**HOLDIT®****MATERIAL SAFETY DATA SHEET****HOLDIT S72***Revised Date: March 2011*

Page 2 of 4

Infosafe No: 5HO0W

Issue Date: June 2005

MODIFIED by HOLDTITE AUSTRALIA

SECTION 4. FIRST AID MEASURES

- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Seek medical attention if irritation or symptoms persist.
- Eye contact:** Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
- Skin contact:** Seek medical attention if irritation or symptoms persist. Wash off immediately with plenty of soap and water.
- Ingestion:** DO NOT INDUCE VOMITING. Drink 1 or 2 glasses of water. Rinse mouth thoroughly. Seek medical attention.

SECTION 5. FIRE FIGHTING MEASURES**5.1 Extinguishing Media:**Alcohol resistant foam. Carbon Dioxide (CO₂). Dry Chemical.**5.2 Special hazards arising from the substance or mixture:**

Burning produces irritating toxic and obnoxious fumes. Carbon dioxides. Cool fire exposed containers with water spray.

5.3 Advice for fire fighters:

In case of fire and/or explosion do not breathe fumes. Protective equipment. Self-contained breathing apparatus. Wear suitable respiratory equipment when necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures.**

Avoid contact with skin and eyes. Ensure adequate ventilation of the working area.

6.2 Environmental precautions

Do not empty into drains; dispose of this material and its containers in a safe way.

6.3 Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labeled containers for disposal.

SECTION 7. HANDLING AND STORAGE**7.1 Precautions for safe handling**

Use only in well ventilated areas. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in the original container in a cool, well ventilated place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Exposure controls****Eye/face protection**

Wear suitable protective clothing, gloves and eye/face protection



HOLDIT
MATERIAL SAFETY DATA SHEET
HOLDIT S72

Revised Date: March 2011

Page 3 of 4

Infosafe No: 5HO0W Issue Date: June 2005

MODIFIED by HOLDTITE AUSTRALIA

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

State	Gel
Colour	White
Odour	Characteristic

SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity Peroxides

SECTION 11. TOXICOLOGY INFORMATION

11.1.4 Toxicological Information

Benzyl, C7 C9 linear branched Alkyl ester, 1, 2, benzene Dicarboxylic Acid	Oral Rat LD50 = 15,800	Dermal Rabbit LD50= 7,940
p-Toluenesulfonyl hydrazide	Oral Mouse LD50 = 283	
Silicone Dioxide	Oral Rat LD50=10,000	Dermal Rabbit LD50=5,000
Triethyleneglycol Dimethacrylate	Dermal Rat LD50 = >5,000	

SECTION 12. ECOLOGICAL INFORMATION

12.1 Toxicity

Triethyleneglycol Dimethacrylate Fish LC50/96h=16.4 mg/l

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal: Follow state or local authority regulations and guidelines for disposal of the waste. Clean area with detergent and water. Do not allow product to enter drains, sewers or water courses – inform the local authorities if this occurs.

Container Disposal: Dispose of as normal industrial waste

SECTION 14. TRANSPORT INFORMATION

ADR/RID	The product is not classified as dangerous for carriage
IMDG	The product is not classified as dangerous for carriage
IATA	The product is not classified as dangerous for carriage

SECTION 15. REGULATORY INFORMATION

Risk Phases	R36/37/38-Irritating to eyes, respiratory system and skin R43 – May cause sensitization by skin contact.
Safety Phases	S24 – Avoid contact with skin S37- Wear suitable gloves



HOLDIT[®]
MATERIAL SAFETY DATA SHEET
HOLDIT S72

Revised Date: March 2011

Page 4 of 4

Infosafe No: 5HO0W

Issue Date: June 2005

MODIFIED by HOLDTITE AUSTRALIA

SECTION 16. OTHER INFORMATION

Text of Risk Phases in Section 3

R21/22 – Harmful in contact with skin and if swallowed

R23 – Toxic by inhalation

R34 – Causes burns

R36/37/38 – Irritating to eyes, respiratory system and skin

R36/38 – Irritating to eyes and skin

R43 – May cause sensitization by skin contact

R48/20/22 – Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R51/53 – Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R7 – May cause fire.

CONTACT POINT

Technical Contact

Numbers:

Head Office Tel: 1300 552 680

****End of MSDS****