



Dynatex[®]

**MATERIAL SAFETY DATA SHEET
DYNATEX 49285**

Revised Date: June 2011

Page 1 of 6

MODIFIED by HOLDTITE AUSTRALIA

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: DYNATEX 49285

Other Names: 49285

Use: General Purpose High quality 100% RTV White Industrial Grade Silicone Sealant

Part Number: 49285 (312gr)

Supplier: Holdtite Australia Pty Ltd
Address: 21 Heath Street
Lonsdale, South Australia, 5160

Emergency Tel: +61 1300 552 680
Telephone: +61 8 8186 0844
Fax: +61 8 8186 0252

Emergency Contact Name:
Emergency Contact Address: See Above Address

Other Information: The information below is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This Company shall not be held liable for any damage resulting from handling or from contact with the above product.

SECTION 2. HAZARDOUS IDENTIFICATION

Primary Routes of Entry Eye contact, inhalation, skin contact

Eye Contact Direct contact may cause moderate irritation.

Skin Contact May cause moderate irritation.

Inhalation Material is not likely to present an inhalation hazard at ambient conditions. However, if material is heated or high vapor/aerosol concentrations are attained, central nervous system depression may occur, which is characterized by drowsiness, dizziness, confusion or loss of coordination.

Ingestion Low ingestion hazard in normal use.

Symptoms of Overexposure No known applicable information.

Existing Conditions Aggravated by Exposure No known applicable information.

Note The above listed potential effects are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for detailed toxicology information.



Dynatex[®]

MATERIAL SAFETY DATA SHEET

DYNATEX 49285

Revised Date: June 2011

Page 2 of 6

MODIFIED by HOLDTITE AUSTRALIA

SECTION 3. COMPOSITION/INFORMATION OF INGREDIENTS

Ingredient CAS Number Weight % ACGIH TLV PEL STEL

Ethyltriacetoxysilane 17689-77-9 1% - 5% TWA 10ppm TWA 10ppm 15ppm

Methyltriacetoxysilane 4253-34-3 1% - 5% TWA 10ppm TWA 10ppm 15ppm

SECTION 4. FIRST AID MEASURES

Eye Contact	Immediately flush with water for 15 minutes. Seek medical attention.
Skin Contact	Remove from skin and wash thoroughly with soap and water or waterless cleanser. Get medical attention if irritation or other ill effects develop or persist.
Inhalation	Material is not likely to present an inhalation hazard at ambient conditions. If material is heated or vapor/mist/dust/fumes are generated, care should be taken to prevent inhalation. In case of exposure to vapor/mist/dust/fumes, move to fresh air.
Ingestion	DO NOT INDUCE VOMITING. Seek immediate medical attention.
Comments	Treat according to person's condition and specifics of exposure.

SECTION 5. FIRE FIGHTING MEASURES

Flash Point	>212F / >100C
FP Method	Closed Cup
Auto-ignition Temperature	Not determined
Flammability Limits in Air	Not determined
Extinguishing Media	On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers.
Special Fire Fighting Procedures	Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.
Unusual Fire or Explosion Hazards	None known
Hazardous Decomposition Products	Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Carbon oxides and traces of incompletely burned carbon compounds Formaldehyde Hydrogen Silicon dioxide Metal oxides



Dynatex[®]

**MATERIAL SAFETY DATA SHEET
DYNATEX 49285**

Revised Date: June 2011

Page 3 of 6

MODIFIED by HOLDTITE AUSTRALIA

SECTION 6. ACCIDENTIAL RELEASE MEASURES

Steps to be taken in case of spill or release

Observe all personal protection equipment recommendations. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

SECTION 7. HANDLING AND STORAGE

Handling Use with adequate ventilation. Product evolves acetic acid with exposed to water or humid air. Provide ventilation during use to control acetic acid with exposure guidelines or use respiratory protection. Avoid eye contact. Avoid skin contact. Do not take internally. Avoid breathing vapor. Keep container closed.

Storage Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Component Exposure Limits Component Name: Ethyltriacetoxysilane
CAS Number: 17689-77-9
Exposure Limits: See acetic acid comments
Component Name: Methyltriacetoxysilane
CAS Number: 4253-34-3
Exposure Limits: See acetic acid comments
Acetic acid is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 10 ppm and ACGIH TLV: TWA 10 ppm, STEL 15 ppm.

Engineering Controls Local Ventilation: Recommended
General Ventilation: Recommended

Eye Protection Use proper protection - safety glasses as a minimum.

Skin Protection Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.
Suitable Gloves: Silver Shield® 4H®

Respiratory Protection Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls.



Dynatex[®]

**MATERIAL SAFETY DATA SHEET
DYNATEX 49285**

Revised Date: June 2011

Page 4 of 6

MODIFIED by HOLDTITE AUSTRALIA

Suitable Respirator	Respiratory protection is not needed under ambient conditions. If vapor/mist/dust/fumes are generated when material is heated or handled, the following is advised. General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR1910.134) and use NIOSH/MSHA approved respirators.
Precautionary Measures	Avoid eye contact. Avoid skin contact. Avoid breathing vapor. Keep container closed. Do not take internally. Use reasonable care.
Comment	Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection.
Note	These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Paste
Specific Gravity	1.007
Color/Appearance	White
Odor	Acetic Acid Odor
pH	Not Determined
Boiling/Cond. Point	Not Determined
Melting/Freezing Point	Not Determined
Solubility	Not Determined
Evaporation Rate	Not Determined
VOC %	29 g/L
Viscosity	Not Determined
Vapor Density	Not Determined
Vapor Pressure	Not Determined
Note	The above information is not intended for use in preparing product specifications. Contact Accumetric LLC before writing specifications.

SECTION 10. STABILITY AND REACTIVITY

Chemical Stability	Stable
Hazardous Polymerization	Will not occur
Conditions to Avoid	None known
Materials to Avoid / Incompatibility	Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous vapors to form.



Dynatex[®]

MATERIAL SAFETY DATA SHEET

DYNATEX 49285

Revised Date: June 2011

Page 5 of 6

MODIFIED by HOLDTITE AUSTRALIA

SECTION 11. TOXICOLOGY INFORMATION

Component Toxicology Information No known applicable information.

Special Hazard Information on Components No known applicable information.

SECTION 12. ECOLOGICAL INFORMATION

Environmental Fate and Distribution Complete information is not yet available.

Environmental Effects Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants Complete information is not yet available.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.
This product is not known to be regulated under RCRA regulations, but contains SARA regulated substances. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Container Disposal: Dispose of as normal industrial waste

SECTION 14. TRANSPORT INFORMATION

DOT Road Shipment Information Not subject to DOT.

Ocean Shipment (IMDG) Not subject to IMDG code.

Air Shipment (IATA) Not subject to IATA regulations.

SECTION 15. REGULATORY INFORMATION

The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA Title III Section 302 Extremely Hazardous Substances None

SARA Title III Section 304 CERCLA Hazardous Substances None



Dynatex[®]

MATERIAL SAFETY DATA SHEET

DYNATEX 49285

Revised Date: June 2011

Page 6 of 6

MODIFIED by HOLDTITE AUSTRALIA

SARA Title III Section 312 Hazard Class Acute: Yes
Chronic: No
Fire: No
Pressure: No
Reactive: No

SARA Title III Section 313 Toxic Chemicals Alumina hydrate (21645-51-2)

Note Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

California Proposition 65 This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None known

Massachusetts Alumina hydrate (21645-51-2)
Silica, amorphous (7631-86-9)
Titanium dioxide (13463-67-7)

New Jersey Alumina hydrate (21645-51-2)
Dimethyl siloxane, hydroxy-terminated (70131-67-8)
Ethyltriacetoxysilane (17689-77-9)
Hydrotreated middle petroleum distillates (64742-46-7)
Methyltriacetoxysilane (4253-34-3)
Silica, amorphous (7631-86-9)
Titanium dioxide (13463-67-7)

Pennsylvania Alumina hydrate (21645-51-2)
Dimethyl siloxane, hydroxy-terminated (70131-67-8)
Hydrotreated middle petroleum distillates (64742-46-7)
Silica, amorphous (7631-86-9)
Titanium dioxide (13463-67-7)

SECTION 16. OTHER INFORMATION

Abbreviations/Acronyms

ADG Code – Australian Code for the Transport of Dangerous Goods by Road and Rail

NOHSC – National Occupational Health and Safety

TWA – Time-Weight Average

CONTACT POINT

Technical Contact

Numbers: Head Office Tel: 1300 552 680

End of MSDS