

**HOLDIT®****MATERIAL SAFETY DATA SHEET  
HOLDIT R69***Revised Date: June 2011*

Page 1 of 4

MODIFIED by HOLDTITE AUSTRALIA

**SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

**Product Name:** HOLDIT R69

**Other Names:** R69 Retainer

**Use:** Low Viscosity General Purpose Retaining Compound

**Part Number:** R69-10 (10ml), R69-50 (50ml), R69-250 (250ml)

**Supplier:** Holdtite Australia Pty Ltd  
**Address:** 21 Heath Street  
Lonsdale, South Australia, 5160

**Emergency Tel:** +61 1300 552 680  
**Telephone:** +61 8 8186 0844  
**Fax:** +61 8 8186 0252

**Emergency Contact  
Address:** See Above Address

**Other Information:** The information below is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This Company shall not be held liable for any damage resulting from handling or from contact with the above product.

**SECTION 2. HAZARDOUS IDENTIFICATION**

**Hazard Category:** Irritant

**Risk Phrases:** R36/38 Irritating to eyes, respiratory system and skin.  
R43 May cause sensitization by skin contact

**Safety Phrases:** S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice  
S27 Take off immediately all contaminated clothing.  
S28 After contact with skin, wash immediately with plenty of water  
S3/14 keep in a cool place.  
S3/9/14 Keep in a cool, well ventilated place away from direct sunlight  
S37 Wear suitable gloves  
S37/39 Wear suitable gloves and eye/face protection  
S39 Wear eye/face protection  
S7 Keep container tightly closed  
S9 Keep container in a well ventilated place



**MATERIAL SAFETY DATA SHEET**  
**HOLDIT R69**

Revised Date: June 2011

Page 2 of 4

MODIFIED by HOLDTITE AUSTRALIA

**SECTION 3. COMPOSITION/INFORMATION OF INGREDIENTS**

Chemical Name	CAS No.	Percent %	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
Methacrylate Esters	NDA-10-235	27813-02-1	15-20	n.e.	n.e.
Polyglycol Dimethacrylate	NDA-10-332	25852-47-5	55-65	n.e.	n.e.
Coumarone Indene Resin	NDA-10-449	Mixture	5-10	n.e.	n.e.
Acrylic Polymer	NDA-10-448	25608-33-7	2-9	n.e.	n.e.
Saccharin	NDA-10-151	81-07-2	0.5-4	n.e.	n.e.
Cumene Hydroperoxide	NDA-10-150	80-15-9	<1	n.e.	n.e.

**SECTION 4. FIRST AID MEASURES**

**Eye Contact:** A primary route of exposure that will cause eye irritation characterized by excessive tearing, redness and blinking.

**FIRST AID:** Flush eyes with generous amounts of water for 15 minutes, lifting both upper and lower eyelids occasionally. Get medical attention.

**Skin Contact:** A primary route of exposure that may cause moderate skin irritation and allergic skin reaction. May cause rash, redness, swelling and blistering (symptoms may be delayed).

**FIRST AID:** Thoroughly wash exposed area with soap and water. Do not use organic solvents on skin. If irritation develops, seek medical attention. Launder clothing before reuse.

**Inhalation:** Not likely route of exposure.

**FIRST AID:** If overcome by exposure, victim should be removed to fresh air immediately. Give artificial respiration as needed. Get immediate medical attention.

**Ingestion:** Ingestion may cause irritation of the gastrointestinal tract.

**FIRST AID:** Do not induce vomiting. Immediately seek medical attention.

**Chronic Effects:** None known.

**Carcinogenic** Contains saccharin which has been determined to cause cancer in laboratory animals.

**SECTION 5. FIRE FIGHTING MEASURES**

**Flash Point:** 200°C PMCC **Auto Ignition Temperature:** Not determined.

**Flammability limits % in Air:** LEL: not determined UEL: Not determined.

**Extinguishing Media:** Use carbon dioxide, foam, dry chemical and/or water spray.

**Special Firefighting:** Wear a NOISH approved self-contained breathing apparatus operated in pressure-demand or other positive pressure when fighting fires. Sealed containers may rupture explosively if exposed to heat.

**Unusual Fire Hazards & Conditions to avoid:** Combustion of product may produce oxides of carbon.

**RECOMMENDED NFA/HMIS RATING**

**Health 2**

**Flammability 1**

**Reactivity 1**

**Personal Protection B**

Note: ratings may differ according to application, environment, and physical state.

**HOLDIT****MATERIAL SAFETY DATA SHEET  
HOLDIT R69**

Revised Date: June 2011

Page 3 of 4

MODIFIED by HOLDTITE AUSTRALIA

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

**Steps to be taken if material is spilled or released:** Absorb material on inert filler, vermiculite, floor absorb or other absorbent material. Transfer to ventilated area and dispose of properly.

**Waste Disposal Methods:** Dispose of material in accordance with local, state and federal regulations.

**Safe Handling & Storage:** Avoid prolonged skin contact. Store product in a cool dry place.

**Other precautions and special hazardous Information:** This material contains inhibitors which upon depletion can result in an excessive thermal reaction.

**SECTION 7. HANDLING AND STORAGE****Precautions for safe handling**

Refer to Section 8 of this MSDS.

**Conditions for safe storage, including any incompatibilities**

Keep only in the original container in a cool, well ventilated place.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Respiratory Protection:** Wear NIOSH/MOSHA approved respirator. Work in a well ventilated area.

**Protective Gloves:** Disposable polyethylene gloves with latex over gloves will give protection.

**Eye Protection:** Wear NIOSH approved safety goggles with side shields or chemical splash goggles.

**Ventilation used:** Local Exhaust.

**Protective Clothing &**

**Equipment:** Wear impervious clothing to prevent repeated, prolonged skin contact.

**Hygienic Work Practices:** Practice good hygiene, and wash hands after using this product.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Boiling Point:** >300°C

**Vapour Density:** >1 Air=1

**VOC:**

**Vapour Pressure:** 5 mmHg @ 26°C

**Density of Coating:**

**Melting Point:** n.a

**Specific Gravity:** 1.10 Water=1

**Evaporation Rate:** n.a

**Water Reactive:** n.a

**Solubility in Water:** Slight

**Appearance:** Green liquid

**Odour:** Sharp Odour.**SECTION 10. STABILITY AND REACTIVITY**

**Stability:** **Stable: x** **Unstable:**

**Hazardous Polymerization:** **May occur:** **will not occur: x**

**Conditions to avoid:** Avoid heat, contact with copper or lead alloy, UV light.

**Incompatibility:** Avoid contact with active metal ions, and heat.

**Hazardous Decomposition Products:** Acrid smoke and fumes.

**HOLDIT****MATERIAL SAFETY DATA SHEET  
HOLDIT R69**

Revised Date: June 2011

Page 4 of 4

MODIFIED by HOLDTITE AUSTRALIA

**SECTION 11. TOXICOLOGY INFORMATION**

<b>Component</b>	<b>ORAL LD50</b>	<b>DERMAL LD50</b>	<b>INHALATION LC50</b>
Methacrylate Esters	11,600 mg/kg (Rat)	Not Determined	Not Determined
Polyglycol Dimethacrylate	Not Determined	Not Determined	Not Determined
Coumarone Indene Resin	Not Determined	Not Determined	Not Determined
Acrylic Polymer	Not Determined	Not Determined	Not Determined
Saccharin	Not Determined	Not Determined	Not Determined
Cumene Hydroperoxide	800-1,600 mg/kg	Severe Irritation	700 ppm Rat

**SECTION 12. ECOLOGICAL INFORMATION**

This product can be harmful to aquatic organisms. Do not allow to contaminate waterways or soil.

**SECTION 13. DISPOSAL CONSIDERATIONS**

**General Information** Local and National regulations. This material and its container must be disposed of in a safe way.

**SECTION 14. TRANSPORT INFORMATION**

<b>ADR/RID</b>	The product is not classified as dangerous for carriage.
<b>IMDG</b>	The product is not classified as dangerous for carriage.
<b>IATA</b>	The product is not classified as dangerous for carriage.

**SECTION 15. REGULATORY INFORMATION**

None Allocated

**SECTION 16. OTHER INFORMATION**

Detaching this notification from the Material Safety Data Sheet is prohibited by law and any copying or distribution of same requires this attachment be included.

This products contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act 1986 and 40 CFR 372:

<u>CAS#</u>	<u>CHEMICAL NAME</u>	<u>% BY WEIGHT</u>
80-15-9	Cumene Hydroperoxide	<3
107-21-1	Ethylene Glycol	

This product contains the following materials that under California Proposition 65 of the Safe Drinking Water and Toxic Enforcement Act of 1986 are recognized to cause cancer or reproductive toxicity.

<u>Material</u>	<u>CAS #</u>	<u>Concentration</u>	<u>Cancer</u>	<u>Reproductive</u>
		<u>%</u>	<u>Agent</u>	<u>Toxin</u>
Ethylene Glycol	107-21-1			X

**CONTACT POINT****Technical Contact**

**Number:** Head Office Tel: 1300 552 680

\*\*End of MSDS\*\*